

Specification Date Sheet | Model: 13EB-EU(W)



ENVIROBULKA 1300 Ltr

Envriobulka static, 110% bunded fuel tank, built to BS799 Part 5 & to comply with PPG2 Regulations

- 110% bunded fuel storage tank to comply with PPG2 (Pollution Prevention Guidelines) Regulations.
- Manufactured to BS799 Part 5- Specification for Oil Storage Tanks.
- Steel tank enclosed in steel, weatherproof outer bund- robust, durable product providing secure storage.
- Fitted with lifting eyes and forkliftable base for ease of handling and relocation of tank (empty only).
- Secure, lockable bund compartment houses pump, nozzle, hoses and feed & return connections. Feed & return hoses can be fed through openings enabling generator to be run whilst compartment locked- helps to prevent theft and vandalism.
- All outlets are mounted above fuel level helping prevent weepage of fuel. Suction pipe to help remove any fluid from the bund.
- Inspection cover provides access to inner tank for maintenance and inspection.

SPECIFICATION

Standard Tank Fittings: 2" vent: 2" fill point: 3" Auxiliary Fill Point: 1 x 1/2" Generator Feed: 2 x 1/2" Return Ports: 1/2" Pump Feed: Gauge: 2 x 1 1/4 " Ports for additional equipment.			
Capacity (Brim Full) Litres:	1300	Weight Unladen (kg):	555
Capacity (Brim Full) Gallons:	285	Weight Laden (kg):	1750*
Dimensions Length (mm):	1537	Design Standards:	BS799 & PPG2
Dimensions Width (mm):	1200	Cabinet Dimensions (mm) Opening Size: Width 855 x Height 450: Depth 451	
Dimensions Height (mm):	1462		
Notes			
*Specific gravity of diesel taken as 0.9 for this calculation.			

Revision Date: 19/02/2015