Specification Date Sheet I Model: 27EB-EU(W)







ENVIROBULKA 2700 Ltr

Envirobulka static, 110% bunded fuel tank, built to BS799 Part 5 & to comply with PPG2 Regulations.

- 110% bunded fuel storage tank to comply with PPG2 (Pollution Prevention Guidelines)
- Manufactured to BS799 Part 5- Specification for Oil Storage Tanks.
- Steel tank enclosed in steel, weatherproof outer bund- robust, durable product providing secure storage.
- Fitted with lifting eyes and forkliftable base for ease of handling and relocation of tank (empty only).
- Secure lockable bund compartment houses pump, nozzle, hoses and feed & return connections. Feed & return hoses can be fed through openings enabling generator to be run whilst compartment locked- helps to prevent theft and vandalism.
- All outlets are mounted above fuel level helping prevent weepage of fuel. Suction pipe to help remove any fluid from the bund.
- Inspection cover provides acess to inner tank for maintenance and inspection.

SPECIFICATION			
Standard Tank Fittings: 2" Vent: 2' x 1 ¼" Ports for additional equipme		Fill Point: 1 x ½" Generator Feed: 2 x ½" Return Posts:1" Pump Feed: Gauge:	: 2
Capacity (Brim Full) Litres:	2700	Weight Unladen (kg): 865	
Capacity (Brim Full) Gallons:	593	Weight Laden (kg): 3268*	
Dimensions Length (mm):	2383	Design Standards: BS799 & PPG2	
Dimensions Width (mm):	1420	Cabinet Dimensions (mm) Opening Size: Width 855 x Height 456: Depth 501	
Dimensions Height (mm):	1499		
		Notes	
	*Specific gravity of	of diesel taken as 0.9 for this calculation	

Revision Date: 19/02/2015



